



A01

Portable baseplate for forklift truck.



A02

Portable baseplate for pallet truck.



A03

Portable baseplate with stabilizers and level.



A04

Off-set column to increase the working area of the Manipulator, complete with mechanical stop every 45°.



A05

Floor built-in runway with pneumatic motor.



A06

Lengthened motorized trolley running on rails to transport the products to be handled.



ACCESSORIES

ACCESSORIES



Up/down brake.



Tooling brake.



Up/down lock.

Booster.



Transport hook.



Proportional valve with handle.



Cycle counter.



Flange allows the customer to fit own tooling onto Manipulator Partner special version.



Weight pre-selector control.



ATTACHMENTS - TRACKS



A22

Overhead tracking system complete of end buffers and composed of two special U shaped profiles in special aluminium alloy, with steel runways and connection and stiffening ribs every 2 mt.



A23

Trolley complete of wheels for the manual running in the tracking system and of drilling plate for the Manipulator attachment.



A24

Trolley running brake.



A25

Compressed-air station to feed the Manipulator along the whole existing tracking system, composed of an air spiral, supporting cable and drive pulley.



A26

Pneumatic motorization of the translation trolley, composed of a pneumatic motor reducer unit with dragging rubber wheel, complete of filter/lubrificator, pressure regulator and push buttons controls for the back and forth running.

BAGS ACCESSORIES



A16

Suction cup for bags complete with rubber lip and lowered controls.



A17

Reducer plate, easy to fasten on the tooling, for handling small bags.



A18

Dust recovery filter mounted on the exhaust piping of the vacuum generator.



A19

Drum filter, attached to the suction piping of the vacuum generator, used to retain the sucked dust.



A20

Silencer mounted on the exhaust pipe of the vacuum generator, used to reduce the noise level by 3 dB(A), from 74 to about 71.